


HWg-SH3

Swing handle cabinet access system with IP interface (WEB) & RFID with database



- ✓ Now you know who and when was in your cabinet. And you know it immediately.
- ✓ Manage RFID cards remotely over the web or central software.
- ✓ Receive SMS or Email with every door opening or attempt to use an unknown card.
- ✓ Open by: SMS, RFID tag, DIN key, Web, or from operator command center

Features

- Controls two cabinet door swing handles
- Built-in WWW interface for configuring the unit and local access to the database
- Online / Offline modes available:
 - 1) **Online mode** requires a central application (HWg-DCD). Card database stored in SH3 along with central software.
 - Offline mode uses an internal authorized card database. Access reported via Email / Syslog.
- Email alerts (Email-2-SMS service)
- Violence (vandalism) detection system
- Log file for all events

Parameters


- Connected peripherals
 - 2 Electr. swing handles SH1 (H3-EM)
 - 2 Door contacts (front / rear / side)
 - o 1 RFID reader (RS-232)
- Internal memory: 100 / 2000 records
- Communication
 - WEB interface for setup & control
 - HWg-DCD protocol supported
- Network Interface: 10/100 Mbps
 HTTP, NTP, SNMP, SMTP, Syslog
- Power: 12V / 0.5A
- Dimensions: 98 x 78 x 31 mm

Applications

- Remote cabinets (remote office)
- Remote sites (highways, BTS...)
- Secure access to datacenters / telco rooms
- Medical cabinets (medicaments storage)

Accessories





HWg SH1 600 358

HWg demo rack 10" 600 395



HWg-SH3 600 402




RFID reader SH3a 600 410



Power adaptor 600 080

Purchase codes				
600 425	HWg-SH3 set	Recommended startup package SH1 swing handle with cable, SH3 unit, RFID reader 232-W1, 2 RFID cards W1, Power adaptor & HWg-DCD software license		
600 395	HWg demo rack 10"HWg Access demo Rack 10" with RFID system and embedded WiFi AP. The best tool for sales & demonstration of rack access system.			
600 358	HWg Swing handle SH1	handle SH1 Southco electronic swing handle (cutout 25 x 150 mm), 4m cable included		
600 410	RFID reader 232-W1	RFID reader 42 x 77.5 mm with 3m cable		
600 433	RFID card W1	One RFID card with printed HWg logo		
600 402	HWg-SH3	SH3 plain model, without accessories		

Online / Offline modes



Comparison of HWg access control solutions

Dor contact SH1 - Electronic Swing Handle Standard cabinet HWg-DCD Central software	Door contact SH1 - Electronic Swing Handle SH3a RFID reader	Standard cabinet	HWg-SH3 HWg-SH3 baccess HWg-DCD Central software
	HWg-SH2	HWg-SH3	Poseidon 4001
Device Web interface	\checkmark	\checkmark	\checkmark
Swing handles + door contacts	\checkmark	\checkmark	\checkmark
Environmental sensors	×	×	\checkmark
M2M (SNMP, XML)	×	×	\checkmark
External lock (dry contact input)	 ✓ 	✓	\checkmark
RFID reader (RS-232 & Wiegand)	×	✓	✓
Internal database of RFID cards	×	✓	×
Local GSM modem (RS-232)	×	×	✓
SMS access & alerts (with HWg-DCD)	\checkmark	✓	✓
Command Center access	 Image: A set of the set of the	 Image: A set of the set of the	\checkmark

